



# Chlorine

This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Date of issue: 01/01/1979    Revision date: 08/16/2018    Supersedes: 11/30/2016

## SECTION: 1. Product and company identification

### 1.1. Product identifier

Product form : Substance  
Substance name : Chlorine

Formula : Cl<sub>2</sub>

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Industrial use; Use as directed.

### 1.3. Details of the supplier of the safety data sheet

Holston Gases, Inc.  
545 W Baxter Ave.  
Knoxville, TN 37921 - USA  
T 1-865-573-1917 - F 1-865-573-0063  
<https://www.holstongases.com/>

### 1.4. Emergency telephone number

Emergency number : Onsite Emergency: 1-800-645-4633

CHEMTREC, 24hr/day 7days/week  
— Within USA: 1-800-424-9300, Outside USA: 001-703-527-3887  
(collect calls accepted, Contract 17729)

## SECTION 2: Hazard identification

### 2.1. Classification of the substance or mixture

#### GHS-US classification

Ox. Gas 1	H270
Press. Gas (Liq.)	H280
Acute Tox. 2 (Inhalation: gas)	H330
Skin Corr. 1A	H314
Eye Dam. 1	H318
STOT SE 3	H335
Aquatic Acute 1	H400

### 2.2. Label elements

#### GHS-US labeling

Hazard pictograms (GHS-US) :



GHS03

GHS04

GHS05

GHS06

GHS07

GHS09

Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H270 - MAY CAUSE OR INTENSIFY FIRE; OXIDIZER  
H280 - CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED  
H314 - Causes severe skin burns and eye damage  
H330 - FATAL IF INHALED  
H400 - VERY TOXIC TO AQUATIC LIFE  
CGA-HG22 - CORROSIVE TO THE RESPIRATORY TRACT

Precautionary statements (GHS-US) :

P202 - Do not handle until all safety precautions have been read and understood.  
P244 - Keep reduction valves/valves and fittings free from oil and grease  
P260 - Do not breathe gas  
P264 - Wash hands thoroughly after handling  
P271+P403 - Use and store only outdoors or in a well-ventilated place.  
P273 - Avoid release to the environment.



# Chlorine

This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Date of issue: 01/01/1979    Revision date: 08/16/2018    Supersedes: 11/30/2016

P280+P284 - Wear protective gloves, protective clothing, eye protection, respiratory protection, and/or face protection.  
P370+P376 - In case of fire: Stop leak if safe to do so  
P405 - Store locked up.  
P501 - Dispose of contents/container Dispose in a safe manner in accordance with local/national regulations  
CGA-PG05 - Use a back flow preventive device in the piping.  
CGA-PG20+CGA-PG10 - Use only with equipment of compatible materials of construction and rated for cylinder pressure.  
CGA-PG12 - Do not open valve until connected to equipment prepared for use.  
CGA-PG18 - When returning cylinder, install leak tight valve outlet cap or plug.  
CGA-PG06 - Close valve after each use and when empty.  
CGA-PG02 - Protect from sunlight when ambient temperature exceeds 52°C (125°F).

## 2.3. Other hazards

Other hazards not contributing to the classification : None.

## 2.4. Unknown acute toxicity (GHS US)

No data available

## SECTION 3: Composition/Information on ingredients

### 3.1. Substances

Name		%
Chlorine (Main constituent)		100

### 3.2. Mixtures

Not applicable

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures after inhalation : Remove to fresh air and keep at rest in a position comfortable for breathing. If not breathing, give artificial respiration. If breathing is difficult, trained personnel should give oxygen. Call a physician. . WARNING: To avoid possible chemical burns, the rescuer should avoid breathing any exhaled air from the victim.

First-aid measures after skin contact : Avoid breathing vapors. In case of contact, immediately flush affected areas with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Call a physician. Wash clothing before reuse. Discard contaminated shoes.

First-aid measures after eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes. Hold the eyelids open and away from the eyeballs to ensure that all surfaces are flushed thoroughly. Contact an ophthalmologist immediately..

First-aid measures after ingestion : Ingestion is not considered a potential route of exposure.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation : Overexposure to concentrations moderately above the TLV of 1 ppm irritates the eyes and respiratory tract. Very brief exposure to a concentration of 1000 ppm may be fatal. Acts as an asphyxiant at high concentrations. Inhalation of high concentrations (e.g, greater than 15 ppm) causes choking, coughing, burning of the throat, and severe irritation of the upper respiratory tract; additionally, pulmonary edema, bronchitis, and pneumonitis may result.

### 4.3. Indication of any immediate medical attention and special treatment needed

Obtain medical assistance.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Oxidizer. May accelerate the burning of other combustible materials.  
Reactivity : No reactivity hazard other than the effects described in sub-sections below.



# Chlorine

This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Date of issue: 01/01/1979    Revision date: 08/16/2018    Supersedes: 11/30/2016

## 5.3. Advice for firefighters

- Firefighting instructions : Evacuate all personnel from the danger area. Use self-contained breathing apparatus (SCBA) and protective clothing. Immediately cool containers with water from maximum distance. Stop flow of gas if safe to do so, while continuing cooling water spray. Remove ignition sources if safe to do so. Remove containers from area of fire if safe to do so. On-site fire brigades must comply with OSHA 29 CFR 1910.156 and applicable standards under 29 CFR 1910 Subpart L—Fire Protection.
- Protection during firefighting : **DANGER! Toxic, corrosive, high-pressure gas..**
- Special protective equipment for fire fighters : Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire fighters.
- Specific methods : Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas containers to rupture. Cool endangered containers with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems.
- Other information : Containers are equipped with a pressure relief device. (Exceptions may exist where authorized by DOT.)
- Stop flow of product if safe to do so.
- Use water spray or fog to knock down fire fumes if possible.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

- General measures : **Danger: Oxidizing gas. Corrosive.** Evacuate personnel to a safe area. Wear a self-contained breathing apparatus and appropriate personal protective equipment (PPE). (gas tight, chemical-protective) Approach suspected leak area with caution. Remove all sources of ignition. Toxic, corrosive vapor can spread from spill. Contact with flammable materials may cause fire or explosion. Ventilate area or move container to a well-ventilated area. Before entering the area, especially a confined area, check the atmosphere with an appropriate device. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous.
- 6.1.1. For non-emergency personnel : No additional information available
- 6.1.2. For emergency responders : No additional information available

### 6.2. Environmental precautions

Prevent waste from contaminating the surrounding environment. Prevent soil and water pollution. Dispose of contents/container in accordance with local/regional/national/international regulations. Contact supplier for any special requirements.

### 6.3. Methods and material for containment and cleaning up

No additional information available

### 6.4. Reference to other sections

See also sections 8 and 13.



# Chlorine

This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Date of issue: 01/01/1979    Revision date: 08/16/2018    Supersedes: 11/30/2016

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Do not breathe gas/vapor. Avoid all contact with skin, eyes, or clothing. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

Wear leather safety gloves and safety shoes when handling cylinders. Protect cylinders from physical damage; do not drag, roll, slide or drop. While moving cylinder, always keep in place removable valve cover. Never attempt to lift a cylinder by its cap; the cap is intended solely to protect the valve. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Never insert an object (e.g. wrench, screwdriver, pry bar) into cap openings; doing so may damage the valve and cause a leak. Use an adjustable strap wrench to remove over-tight or rusted caps. Slowly open the valve. If the valve is hard to open, discontinue use and contact your supplier. Close the container valve after each use; keep closed even when empty. Never apply flame or localized heat directly to any part of the container. High temperatures may damage the container and could cause the pressure relief device to fail prematurely, venting the container contents. For other precautions in using this product, see section 16.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Avoid oil, grease and all other combustible materials.

Store only where temperature will not exceed 125°F (52°C). Post "No Smoking/No Open Flames" signs in storage and use areas. There must be no sources of ignition. Separate packages and protect against potential fire and/or explosion damage following appropriate codes and requirements (e.g. NFPA 30, NFPA 55, NFPA 70, and/or NFPA 221 in the U.S.) or according to requirements determined by the Authority Having Jurisdiction (AHJ). Always secure containers upright to keep them from falling or being knocked over. Install valve protection cap, if provided, firmly in place by hand when the container is not in use. Store full and empty containers separately. Use a first-in, first-out inventory system to prevent storing full containers for long periods. For other precautions in using this product, see section 16.

**OTHER PRECAUTIONS FOR HANDLING, STORAGE, AND USE:** When handling product under pressure, use piping and equipment adequately designed to withstand the pressures to be encountered. Never work on a pressurized system. Use a back flow preventive device in the piping. Gases can cause rapid suffocation because of oxygen deficiency; store and use with adequate ventilation. If a leak occurs, close the container valve and blow down the system in a safe and environmentally correct manner in compliance with all international, federal/national, state/provincial, and local laws; then repair the leak. Never place a container where it may become part of an electrical circuit.

### 7.3. Specific end use(s)

None.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

Chlorine (7782-50-5)		
ACGIH	ACGIH TLV-TWA (ppm)	0.1 ppm
ACGIH	ACGIH TLV-STEL (ppm)	0.4 ppm
USA OSHA	OSHA PEL (Ceiling) (mg/m <sup>3</sup> )	3 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (Ceiling) (ppm)	1 ppm
USA IDLH	US IDLH (ppm)	10 ppm

### 8.2. Exposure controls

Appropriate engineering controls : Use only in a closed system. A corrosion-resistant, forced-draft fume hood is preferred. LOCAL EXHAUST: A corrosion-resistant system is acceptable.

Eye protection : Wear safety glasses with side shields. Wear goggles and a face shield when transfilling or breaking transfer connections. Provide readily accessible eye wash stations and safety showers. Wear safety glasses with side shields or goggles when transfilling or breaking transfer connections.



# Chlorine

This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Date of issue: 01/01/1979    Revision date: 08/16/2018    Supersedes: 11/30/2016

Skin and body protection	: Wear metatarsal shoes and work gloves for cylinder handling, and protective clothing where needed. Wear appropriate chemical gloves during cylinder changeout or wherever contact with product is possible. Select per OSHA 29 CFR 1910.132, 1910.136, and 1910.138.
Respiratory protection	: When workplace conditions warrant respirator use, follow a respiratory protection program that meets OSHA 29 CFR 1910.134, ANSI Z88.2, or MSHA 30 CFR 72.710 (where applicable). Use an air-supplied or air-purifying cartridge if the action level is exceeded. Ensure that the respirator has the appropriate protection factor for the exposure level. If cartridge type respirators are used, the cartridge must be appropriate for the chemical exposure. For emergencies or instances with unknown exposure levels, use a self-contained breathing apparatus (SCBA).
Thermal hazard protection	: Wear cold insulating gloves when transfilling or breaking transfer connections.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Gas
Appearance	: Greenish-yellow gas. Amber liquid.
Molecular mass	: 71 g/mol
Color	: Greenish gas.
Odor	: Pungent.
Odor threshold	: Odor threshold is subjective and inadequate to warn for overexposure. 0.23 mg/m <sup>3</sup> (Dixon and Ikels)
pH	: Not applicable.
Relative evaporation rate (butyl acetate=1)	: No data available
Relative evaporation rate (ether=1)	: Not applicable.
Melting point	: -101 °C (-149.85°F)
Freezing point	: No data available
Boiling point	: -34.05 °C (-29.25°F)
Flash point	: Not applicable.
Critical temperature	: 144 °C
Auto-ignition temperature	: Not applicable.
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: 6.9 bar (100 psia) (@20°C [68°F])
Critical pressure	: 77.11 bar (1118.4 psia)
Relative vapor density at 20 °C	: No data available
Relative density	: 1.6
Density	: 2.7 kg/m <sup>3</sup> (at 50 °C)
Relative gas density	: 2.5
Solubility	: Water: 8620 mg/l
Log Pow	: Not applicable.
Log Kow	: Not applicable.
Viscosity, kinematic	: Not applicable.
Viscosity, dynamic	: Not applicable.
Explosive properties	: Not applicable.
Oxidizing properties	: Oxidizer.
Explosion limits	: Non flammable.

### 9.2. Other information

Gas group	: Press. Gas (Liq.)
Additional information	: Gas/vapor heavier than air. May accumulate in confined spaces, particularly at or below ground level.



# Chlorine

This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Date of issue: 01/01/1979    Revision date: 08/16/2018    Supersedes: 11/30/2016

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No reactivity hazard other than the effects described in sub-sections below.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

May occur.

### 10.4. Conditions to avoid

Air contact. High temperature. Moisture. Incompatible materials.

### 10.5. Incompatible materials

Chlorine reacts with most materials, especially flammable materials, other reducing agents, and nearly all metals. At temperatures below 250°F (121°C) certain common metals (e.g. iron, copper, steel, lead, nickel) resist reaction with dry chlorine, but others (e.g. aluminum, arsenic, gold, mercury, tin, titanium) react. Moist chlorine is highly corrosive except to glass, stoneware, porcelain, and certain alloys and only at low pressure. Titanium ignites spontaneously on contact with dry chlorine. Carbon steel ignites in chlorine at temperatures near 483°F (251°C).

### 10.6. Hazardous decomposition products

Toxic fumes. Chlorides.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Inhalation:gas: FATAL IF INHALED.

Chlorine (lf) 7782-50-5	
LD50 oral rat	6800 mg/kg
LC50 inhalation rat (ppm)	146.5 ppm/4h
ATE US (gases)	146.5 ppmV/4h

Skin corrosion/irritation	: Causes severe skin burns and eye damage. pH: Not applicable.
Serious eye damage/irritation	: CAUSES SERIOUS EYE DAMAGE. pH: Not applicable.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity – single exposure	: May cause respiratory irritation.
Specific target organ toxicity – repeated exposure	: Not classified
Aspiration hazard	: Not classified
Symptoms/effects after inhalation	: Overexposure to concentrations moderately above the TLV of 1 ppm irritates the eyes and respiratory tract. Very brief exposure to a concentration of 1000 ppm may be fatal. Acts as an asphyxiant at high concentrations. Inhalation of high concentrations (e.g. greater than 15 ppm) causes choking, coughing, burning of the throat, and severe irritation of the upper respiratory tract; additionally, pulmonary edema, bronchitis, and pneumonitis may result.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : VERY TOXIC TO AQUATIC LIFE.

Chlorine (7782-50-5)	
LC50 fish 1	0.44 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [flow-through])



# Chlorine

This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Date of issue: 01/01/1979    Revision date: 08/16/2018    Supersedes: 11/30/2016

## Chlorine (7782-50-5)

EC50 Daphnia 1	0.017 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 fish 2	0.14 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through])

## 12.2. Persistence and degradability

### Chlorine (7782-50-5)

Persistence and degradability	Not applicable for inorganic gases.
-------------------------------	-------------------------------------

## 12.3. Bioaccumulative potential

### Chlorine (7782-50-5)

BCF fish 1	(no bioaccumulation expected)
Log Pow	Not applicable.
Log Kow	Not applicable.
Bioaccumulative potential	No data available.

## 12.4. Mobility in soil

### Chlorine (7782-50-5)

Mobility in soil	No data available.
Ecology - soil	Because of its high volatility, the product is unlikely to cause ground or water pollution.

## 12.5. Other adverse effects

Other adverse effects	: May cause pH changes in aqueous ecological systems.
Effect on ozone layer	: None.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Product/Packaging disposal recommendations : Do not attempt to dispose of residual or unused quantities. Return container to supplier.

## SECTION 14: Transport information

In accordance with DOT

Transport document description	: UN1017 Chlorine, 2.3
UN-No.(DOT)	: UN1017
Proper Shipping Name (DOT)	: Chlorine
Class (DOT)	: 2.3 - Class 2.3 - Poisonous gas 49 CFR 173.115
Hazard labels (DOT)	: Poison Gas 2.3 - Poison gas





# Chlorine

This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Date of issue: 01/01/1979    Revision date: 08/16/2018    Supersedes: 11/30/2016

- DOT Special Provisions (49 CFR 172.102) : 2 - This material is poisonous by inhalation (see 171.8 of this subchapter) in Hazard Zone B (see 173.116(a) or 173.133(a) of this subchapter), and must be described as an inhalation hazard under the provisions of this subchapter.  
 B9 - Bottom outlets are not authorized.  
 B14 - Each bulk packaging, except a tank car or a multi-unit-tank car tank, must be insulated with an insulating material so that the overall thermal conductance at 15.5 C (60 F) is no more than 1.5333 kilojoules per hour per square meter per degree Celsius (0.075 Btu per hour per square foot per degree Fahrenheit) temperature differential. Insulating materials must not promote corrosion to steel when wet.  
 N86 - UN pressure receptacles made of aluminum alloy are not authorized.  
 T50 - When portable tank instruction T50 is referenced in Column (7) of the 172.101 Table, the applicable liquefied compressed gases are authorized to be transported in portable tanks in accordance with the requirements of 173.313 of this subchapter.  
 TP19 - The calculated wall thickness must be increased by 3 mm at the time of construction. Wall thickness must be verified ultrasonically at intervals midway between periodic hydraulic tests (every 2.5 years). The portable tank must not be used if the wall thickness is less than that prescribed by the applicable T code in Column (7) of the Table for this material.
- Marine pollutant : P



### Additional information

- Emergency Response Guide (ERG) Number : 124;173
- Other information : No supplementary information available.
- Special transport precautions : Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers:  
 - Ensure there is adequate ventilation. - Ensure that containers are firmly secured. - Ensure cylinder valve is closed and not leaking. - Ensure valve outlet cap nut or plug (where provided) is correctly fitted. - Ensure valve protection device (where provided) is correctly fitted.

### Transport by sea

- UN-No. (IMDG) : 1017
- Proper Shipping Name (IMDG) : CHLORINE
- Class (IMDG) : 2 - Gases
- Division (IMDG) : 2.3 - Toxic gases
- MFAG-No : 124

### Air transport

- UN-No. (IATA) : 1017
- Proper Shipping Name (IATA) : CHLORINE
- Class (IATA) : 2
- Civil Aeronautics Law : Gases under pressure/Gases toxic under pressure

## SECTION 15: Regulatory information

### 15.1 US Federal regulations

<b>Chlorine (7782-50-5)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Listed on the United States SARA Section 302	
Subject to reporting requirements of United States SARA Section 313	
CERCLA RQ	10 lb
SARA Section 302 Threshold Planning Quantity (TPQ)	100 lb





# Chlorine

This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Date of issue: 01/01/1979    Revision date: 08/16/2018    Supersedes: 11/30/2016

## Chlorine (7782-50-5)

SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Delayed (chronic) health hazard Sudden release of pressure hazard Fire hazard
SARA Section 313 - Emission Reporting	1 %

## 15.2 International regulations

### CANADA

#### Chlorine (7782-50-5)

Listed on the Canadian DSL (Domestic Substances List)

### EU-Regulations

#### Chlorine (7782-50-5)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

### 15.2.2. National regulations

#### Chlorine (7782-50-5)

Listed on the AICS (Australian Inventory of Chemical Substances)  
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)  
Listed on the Korean ECL (Existing Chemicals List)  
Listed on NZIoC (New Zealand Inventory of Chemicals)  
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)  
Japanese Poisonous and Deleterious Substances Control Law  
Listed on the Canadian IDL (Ingredient Disclosure List)  
Listed on INSQ (Mexican National Inventory of Chemical Substances)  
Listed on CICR (Turkish Inventory and Control of Chemicals)  
Listed on the TCSI (Taiwan Chemical Substance Inventory)

## 15.3. US State regulations

### Chlorine(7782-50-5)

U.S. - California - Proposition 65 - Carcinogens List	No
U.S. - California - Proposition 65 - Developmental Toxicity	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Female	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No
State or local regulations	U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List U.S. - Pennsylvania - RTK (Right to Know) List



# Chlorine

This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Date of issue: 01/01/1979    Revision date: 08/16/2018    Supersedes: 11/30/2016

## SECTION 16: Other info.

### Other information

When you mix two or more chemicals, you can create additional, unexpected hazards. Obtain and evaluate the safety information for each component before you produce the mixture. Consult an industrial hygienist or other trained person when you evaluate the end product. Before using any plastics, confirm their compatibility with this product.

Holston Gases asks users of this product to study this SDS and become aware of the product hazards and safety information. To promote safe use of this product, a user should (1) notify employees, agents, and contractors of the information in this SDS and of any other known product hazards and safety information, (2) furnish this information to each purchaser of the product, and (3) ask each purchaser to notify its employees and customers of the product hazards and safety information.


The opinions expressed herein are those of qualified experts within Holston Gases, Inc. We believe that the information contained herein is current as of the date of this Safety Data Sheet. Since the use of this information and the conditions of use are not within the control of Holston Gases, Inc, it is the user's obligation to determine the conditions of safe use of the product.

Holston SDSs are furnished on sale or delivery by Holston Gases or the independent distributors and suppliers who package and sell our products. To obtain current SDSs for these products, contact your Holston Gases sales representative, local distributor, or supplier, or download from [www.holstongases.com](http://www.holstongases.com). If you have questions regarding Holston SDSs, would like the document number and date of the latest SDS, or would like the names of the Holston suppliers in your area, phone or write the Holston Gases Call Center (Phone: 1-865-573-1917; Address: Holston Gases Inc., 545 W Baxter Ave #6846, Knoxville, TN 37921 )

Holston Gases Inc and the Flowing Airstream design are trademarks or registered trademarks of Holston Gases Inc. Technology, Inc. in the United States and/or other countries.

Revision date : 08/16/2018

- NFPA health hazard : 4 - Materials that, under emergency conditions, can be lethal.
- NFPA fire hazard : 0 - Materials that will not burn under typical dire conditions, including intrinsically noncombustible materials such as concrete, stone, and sand.
- NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.
- NFPA specific hazard : OX - Materials that posses oxidizing properties.



### Hazard Rating

- Health : 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given
- Flammability : 0 Minimal Hazard
- Physical : 2 Moderate Hazard

SDS US (GHS HazCom 2012) - Holston Gases

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*